



## AGX-PA350Ex 125kHz Antenna ATEX Zone 1



powered by TECTUS

<b>Product Description</b>		<b>AGX-350Ex-LF Fix mount antenna</b>
<b>Electrical Characteristics</b>		
Description:	LF antenna for use in potentially explosive atmospheres	
Operating Frequency	LF 125kHz	
Supported Reader	<b>AGX 35Ex</b>	
<b>Thermal &amp; Environmental Characteristics</b>		
Operating Temperature	-20°C up to +60°C	
Read Distance:	Up to 300 mm	
<b>Physical Characteristics</b>		
Housing:	Plastic Black	
Dimensions:	350 x 150 x 25 mm	
Weight:	2 kg	
IP Class	IP67	
Specials:	Aircoil Antenna	
Ex Marking:	BVS 05 ATEX E 004 X E II 2G EEx m II T4 CE 0158 E I M2 EEx m I -20 °C < Ta < 60 °C	
<b>Article no:</b>		
Article no:	<b>AGX-PA350Ex</b>	
<b>Typical Applications</b>		
All LF RFID applications in ATEX Zones I & II		

**AGILLOX GmbH**  
 Hopfensiegelweg 8  
 D-84072 Au i. d. HALLERTAU  
 Tel: +49 8752 869911  
 Fax: +49 8752 8657931

**Contact:**  
 sales@agillox.com  
 www.agillox.com