



AGX DAP9700 (ELV) RUGGED Tablet PC







Product Description

Performance Windows® Embedded 7 Tablet PC 9.7"

Brilliant, large multi-touch Display in a lightweight rugged Tablet PC

The AGX DAP9700 rugged tablet combines form and function in a lightweight mobile tablet. With an eye-catching 9.7 inch display and its rugged construction, the Windows® tablet ships ready for enterprise.

Large, brilliant display—full 9.7 inch multi-touch display for pan and zoom functions.

Windows Embedded Standard 7 operating system—allows for seamless migration into most enterprise environments.

User-friendly form factor—delivers lightweight mobility in a rugged tablet that is just over 2 pounds (989 g) and less than an inch thick (22 mmm).

IP54 certified and MIL-STD-810F—Protected against water, dust, and 4 foot drops to concrete, offering a more durable solution than consumer tablets and enabling use in a variety of environments.

Multiple communications options—WLAN, Bluetooth and optional WWAN 3 G and GPS.

RFID Optional USB (LF, HF and UHF) or via BT

The AGX DAP9700 can be enhanced over the USB Slot with various RFID USB Dongle Reader (LF, HF and UHF). In addition it combines perfectly over the Bluetooth connection with handy BT reader like AGX DOT900 (UHF) or any other BT device.

^{*} in preparation LF, HF and UHF

Article no:		AGX DAP9700
Typical Applications		
Manufacturing	•Health Care	Vehicle Maintenance and Diagnostics
•Finance	Education	•Automotive •Security
•Gaming	Hospitality	•Retail and POS
•Insurance	 Transportation 	Home Automation



Technical Specifications	AGX DAP9700 (ELV)

Operating System	Windows® Embedded Standard 7	
Processor	Intel® Atom™ N2600 dual core 1.6 GHz	
Memory	2 GB DDR3-800	
Storage	32 GB solid state drive	
Display	9.7 inch XVGA (1024 x 768) IPS LED panel, 350 nits, sunlight viewable (optional), Multi-touch capacitive touchscreen (four point) sunlight viewable (optional)	
Keypad and Buttons	Power button, programmable function key, menu key, volume up/down keys, LED indicator (power, battery, HDD access, WiFi)	
WLAN	802.11 b/g/n	
WWAN	Optional 3 G module	
GPS	Optional GPS module	
Bluetooth	v2.1 + EDR Class II	
Input/Output	Power jack 1 x USB 2.0 1 x LIF connector (Ethernet or HDMI via dongle)	
Expansion Slots	SIM Card slot	
Data Capture	2 MP color camera with autofocus and flash	
Audio	2 x 1 W speakers HD Audio 1 x stereo headset jack	
Battery	Internal Li-ion 5300 mAh	
Input	12 VDC	
Adapter	100–240 V, 50-60 Hz / 12 V DC input	
Dimensions	10.5 (L) × 8.3 (W) × 0.8 (H) inches [267 × 210 × 22 mm]	
Weight	2.18 lb. [988 g]	
Regulatory	FCC class B, CE, EN60601-1-1, EN60601-1-2	
Operating temperature	32 to +122 °F [0 to +50 °C]	
Charging temperature	32 to +113 °F [0 to +45 °C]	
Drop	Multiple 4 foot (1.2 m) drops to concrete	
ESD	15 kV air discharge, 8 kV direct discharge	
Sealing	IP54 certified	
Humidity	30 % - 90 %, non-condensing	
Vibration	MIL-STD-810F	

AGX DAP 9700 Accessories







HDMI Adapter



Vehicle Charger



Carry Case



Desktop Dock



Charging Cart



Hand Strap