



AGX XS7

Mini GPS Tracker

| | |
|---|---|
| Product name | AGX XS7 |
| Technical data | |
| Module: | Combined GSM Quad-Band / GPS Modul |
| Antennas: | GSM/GPRS and GPS (ceramic) integrated |
| Communication: | Communication via TCP/IP (GPRS based) |
| GPS Type: | A-GPS |
| Indicators: | LED for GSM, GPS, Battery and Alarming |
| Interface | |
| PC Interface: | USB |
| Electrical specifications | |
| Power supply: | 5V or over USB |
| Battery | High Power Li-Polymer battery 66mAH (1320mAH optional) |
| Operational temperature: | -20° up to +60° C (Charging: 0°C up to +45°C) |
| Storage temperature: | -30° up to +70° C |
| Humidity: | 0-95%, not condensierend |
| Size: | 57 x 38 x 15mm |
| Weight: | 35 g |
| Optionen: | 3-D sensor; Sensor for movement, direction, (+/- 8g) |
| External Interface | |
| Examples for battery life time: | <p>Examples „standby time“—all data with perfect GPS/GSM (GPRS) conditions!</p> <p>GSM deep sleep: Motion event => approx. >5 month</p> <p>GSM sleep timer (GSM low power inactiv): 4h time interval => approx. 3 weeks</p> <p>Full power (sleep mode inactive; GSM low power active): 5min time interval => approx. 12h</p> <p>Full power (sleep mode inactive; GSM low power inactive): 15sec time interval => approx. 7h</p> <p>Real-time tracking (every second): more than 11.500 position messages => approx. 2:50 – 3:15h</p> |
| Certification: | CE, Rohs |
| Articel No: | AGX XS7 |
| Typical Applications: | |
| Vehicle protection (bicycle, motorbike, car, truck etc) | |
| People protection (children, VIP's, eledry people or animals) | |
| Automatic vehicle location | |
| Tracking of valuable goods | |

Contact:

sales@agilox.com
www.agilox.com