


DATA SHEET



ATEX FIT400P Tag



Zone 0

Product Description		ATEX FIT400P Tag
Physical Specifications		
Encasement	Durable Paint	
Size (mm) (tolerance)	17.6 x 7.1 x 4.1mm +/- 0.5 / 0.70 x 0.28 x 0.16in +/-0.02	
Weight	3.5gr	
RF Specifications		
Protocol	EPC Class 1 Gen2	
Frequency Range (MHz)	866-868 (EU) / 902-928 (US)	
Read Range (Fixed reader) 1	Up to 3.5m (11.5ft)	
Read Range (Handheld reader) 1	Up to 1.75m (5.7ft)	
Material Compatibility	Plastic and non-metallic substrates	
IC Type (chip)	Alien H3	
Memory 2	EPC - 96bits, User - 512bits, TID - 64bits	
Environmental Specification		
Operating Temperature	-40 to +85 °C	
Long term Max Temperature 1 exposure - (days,weeks,years)	+120 °C	
Short term Max Temperature 1 exposure - (minutes,hours)	+150 °C	
IP Rating	IP68	
Shock and Vibration	MIL STD 810-F	
Impact	5kg from 1m	
Attachment	Permanent liquid adhesive (not included) Film adhesive (option)	
Certifications	RoHS approved CE approved ATEX/IECEx certified (option) US&Canada (C1D1/D2) certified (option)	
ATEX	 <p>II 1G Ex ia IIA Ga I M1 Ex ia Ma</p>	
Article no:		
Article no:	ATEX FIT400P Tag	
Typical Applications		
Suitable for metal environment	Offshore	
Maintenance & Service	Oil & Gas	
Industrie & Logistics	Chemical Industry	

Contact:

sales@agillox.com
www.agillox.com