



Cylinder Tag

Product Description		Cylinder Tag					
Electrical Characteristics							
Operating Frequency	125KHz / 13,56MHz						
IC Technologies	NXP, LEGIC, EM MARIN, ATMEL						
Memory Size	Depends on IC type						
Thermal & Environmental Characteristics							
Storage Temperature	-40°C up to +100°C						
Operating Temperature	-40°C up to +85°C						
Packaging Protection Class	IP 67						
Shock & Vibration	IEC 68-2-6 / 29						
RoHs Compliance	YES						
Physical Characteristics							
Available Size	44,50 mm	46 mm	52 mm	56,50 mm	62,50 mm	72 mm	77,50 mm
Outer Diameter	44,50 mm	46,0 mm	52,0 mm	56,50 mm	62,50 mm	72,0 mm	77,50 mm
Inner Diameter	28,0 mm	30,0 mm	35,0 mm	40,0 mm	45,0 mm	54,50 mm	60,0 mm
Thickness	3,0 mm	3,0 mm	3,25 mm	3,0 mm	3,0 mm	3,0 mm	3,0 mm
Weight (approx.)	3,8 gr	4,0 gr	4,6 gr	5,2 gr	6,0 gr	8,0 gr	9,0 gr
Material	Special Thermoplastic + Epoxy						
Article no:							
Article no:	CT001	CT002	CT003	CT004	CT005	CT006	CT007
Typical Applications							
Beer Containers							
Bottle Tagging							
Cylinders							