



## Epoxy Potted Tag

<b>Product Description</b>		<b>Epoxy Potted Tag</b>				
<b>Electrical Characteristics</b>						
Operating Frequency		125KHz / 13,56MHz				
IC Technologies		NXP, LEGIC, EM MARIN, ATMEL				
Memory Size		Depends on IC type				
<b>Thermal &amp; Environmental Characteristics</b>						
Storage Temperature		-40°C up to +100°C				
Operating Temperature		-40°C up to +85°C				
Packaging Protection Class		IP 67				
Shock & Vibration		IEC 68-2-6 / 29				
RoHs Compliance		YES				
<b>Physical Characteristics</b>						
Available Size	12 mm	16 mm	20 mm	25 mm	30 mm	50 mm
Outer Diameter	12,0 mm	16,0 mm	20,0 mm	25,0 mm	30,0 mm	50,0 mm
Inner Diameter	N.A.	N.A.	N.A.	N.A.	N.A.	5mm
Thickness	5,0 mm	2,9 mm	2,7 mm	5,0 mm	3,0 mm	5,1 mm
Weight	0,8 gr	0,8 gr	1,1 gr	1,8 gr	2,6 gr	14,40 gr
Material	Special Thermoplastic + Epoxy					
<b>Article no:</b>						
Article no:	EPT001	EPT002	EPT003	EPT004	EPT005	EPT006
<b>Typical Applications</b>						
Slaughter house						
Rental						
Maintenance & Service						
Warehouse & Logistics						
Industrie & Logistics						