DATA SHEET

Injectable Tag

Product Description	Injectable Tag
Electrical Characteristics	
Operating Frequency	134,2KHz FDX-B ISO11784/85
IC Technologies	NXP, EM MARIN
Memory Size	Depends on IC type
Thermal & Environmental Characteristics	
Storage Temperature	-40ºC up to +100ºC
Operating Temperature	-40ºC up to +85ºC
Packaging Protection Class	IP 68
Shock & Vibration	IEC 68-2-6 / 29
RoHs Compliance	YES

Physical Characteristics

Available Size	12 mm	14 mm	22 mm	32 mm	34 mm
Length	12,0 mm	14,0 mm	22,0 mm	32,0 mm	34,0 mm
Thickness	2,0 mm	3,0 mm	4,0 mm	4,0 mm	4,0 mm
Weight	0,2 gr	0,3 gr	0,6 gr	0,9 gr	1,0 gr
Material	Bioglas & Epoxy				
Colour	Transparent				

Article no:

Article no:	INT001	INT002	INT003	INT004	INT005

Typical Applications

Livestock
Food & animal

AGILLOX GmbH
Hopfensiegelweg 8
D-84072 Au i. d. HALLERTAU
Tel: +49 8752 869911
Fax: +49 8752 8657931

Contact:

sales@agillox.com
www.agillox.com